

5003 密碼 DddcAj2p

5004 密碼 nsV4FPTN

System Configuration

Set Administrator Settings menu password.

Search...

SIP

Refresh

Collapse all

Expand all

- Audio
- Cameras
- Conference
- FacilityService
- H323
- Logging
- Network
- NetworkServices
- Peripherals
- Phonebook Server
- Provisioning
- RTP Ports Range
- Security
- SerialPort
- SIP**
- Standby
- SystemUnit
- Time
- UserInterface
- Video

ANAT	Off	▼
AuthenticateTransferor	Off	▼
ListenPort	On	▼
PreferredIPMedia	IPv4	▼
PreferredIPSignaling	IPv4	▼

OCSP		
DefaultResponder	<input type="text"/>	(0 to 255 characters)
Mode	Off	▼

Profile 1		
DefaultTransport	UDP	▼
DisplayName	5004	(0 to 255 characters)
Line	Private	▼
Mailbox	<input type="text"/>	(0 to 255 characters)
Outbound	Off	▼

TlsVerify	Off	▼
Type	Standard	▼
URI	5004@210.200.7.140	(0 to 255 characters)

Authentication 1		
LoginName	5004	(0 to 128 characters)
Password	nsV4FPTN	Clear (0 to 128 characters)

Ice		
DefaultCandidate	Host	▼
Mode	Auto	▼

Proxy 1		
Address	210.200.7.140	(0 to 255 characters)
Discovery	Manual	▼

Proxy 2		
Address	<input type="text"/>	(0 to 255 characters)
Discovery	Manual	▼

Proxy 3		
Address	<input type="text"/>	(0 to 255 characters)
Discovery	Manual	▼

Proxy 4

Address (0 to 255 characters)

Discovery ▾

Turn

BandwidthProbe ▾

DiscoverMode ▾

DropRfix ▾

Password (0 to 128 characters)

Server (0 to 255 characters)

UserName (0 to 128 characters)